USB KVM SWITCH 2-PORT

Vision | **331522**

Requirements

Console

- A VGA monitor of the highest resolution that you will be using on any computer in the installation
- A USB Keyboard
- A USB Mouse

Computers

The following equipment must be installed on each computer that is to be connected to the system:

- A VGA video port
- USB 1.1/2.0 port * 2

Installation

Important

- Before you begin, make sure that the power to all the devices you will be connecting has been turned off. You must unplug the power cords of any computers that have the Keyboard Power On function. Otherwise, the switch will receive power from the computer.
- To prevent damage to your equipment, make sure that all the devices you will be connecting are properly grounded.

Installing your new USB Cable KVM Switch involves the following steps:

1. Plug your keyboard, monitor, and mouse into the Console ports of the KVM Switch. Each port is labeled with an appropriate icon.
2. Connect the KVM's VGA cable to the VGA port on one of your computer.
3. Connect 2 USB connectors on the same cable to the same computer.
4. Repeat step 2 and 3 on the other computer.
5. Boot the computers.
6. Tap the remote switch button to switch between computers.

Note: The Power On default of KVM Switch is link to the first computer you turn on.

Operation

Place your Remote Switch on the desktop; tap the remote switch button to switch between computers.

Specifications

Computer Connections	2
Port Selection	Wired Remote Switch, (1.8m)
Video	2048 x 1536; DDC2B
Connectors	**Console Ports** Keyboard: 1 x USB Type A Female (Black) Video: 1 x HDB-15 Female (Blue) Mouse: 1 x USB Type A Female (Black) **KVM Ports** Keyboard/ Mouse: 4 x USB Type A Male (Black) Video: 2 x HDB-15 Male (Blue)
LEDs	Selected: 2 (Green)
Cable Length	Computers: 1.2m
Emulation	Keyboard/ Mouse: USB
Environment	Operating Temp.: 0-50°C Storage Temp.: -20-60°C Humidity: 0-80% RH, Non-condensing
Physical Properties	Housing: Plastic Weight: 357g Dimensions (W x D x H): 78 x 72x 24 cm